

WEATHER SHIELD.

WINDOWS & DOORS

Quick Spec Guide

Classic Series™ Direct Set

| SPECIFICATION | STANDARD FEATURES | OPTIONAL FEATURES |
|-------------------------|---|--|
| EXTERIOR FINISH | <ul style="list-style-type: none"> Natural White Black Mocha Putty Iron Ore Portobello | <ul style="list-style-type: none"> White Forest Green Fossil Red Iron Beige Wolf Gray |
| EXTERIOR TRIM | <ul style="list-style-type: none"> Fold out Fin | <ul style="list-style-type: none"> Brickmold 3 1/2" Brickmold 3 1/2" Flat Casing Jefferson Monroe 1/2" Sill Nosing 1" Sill Nose 2" Sill Nose |
| INTERIOR FINISH | <ul style="list-style-type: none"> Natural | <ul style="list-style-type: none"> Clear Satin Primed - White Prefinished White Prefinished Black |
| INTERIOR SPECIES | <ul style="list-style-type: none"> Pine | |
| SHAPE/SIZE | <p>Shapes available include, Rectangle, Pentagon, Trapezoid, Isosceles Triangle, Offset Triangle, Right Triangle, Truncated Triangle, Flat Top Trapezoid, Flat Top Pentagon, Octagon, Hexagon, Parallelogram, Half Circle, Qtr Circle, Eyebrow, Qtr Eyebrow, Ellipse, Half Ellipse, Half Circle w/ legs, Qtr Circle, w/ legs, Eyebrow w/ legs, Qtr Eyebrow w/ legs, Gothic w/ legs, Full Circle, Oval</p> | <ul style="list-style-type: none"> Custom jamb sizes from 8" to 144" Minimum Radius is 12" Minimum Corner Angle is 21 degrees: |
| GLAZING | <ul style="list-style-type: none"> Low-E Insulating Glass | <ul style="list-style-type: none"> Low-E Extreme Zo-e-shield 5 Zo-e-shield Extreme Passive Solar Low-E Passive Solar Low-E Extreme Obscure Tempered |
| GRILLES | | <ul style="list-style-type: none"> GBG: 3/4" Contour SDL: 7/8" |
| JAMB | <ul style="list-style-type: none"> 3-11/16" | <ul style="list-style-type: none"> 3-11/16 Min 9-3/16" Max |

WEATHER SHIELD.

WINDOWS & DOORS